

SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 453/2010

Powder T/SWIM

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Powder T/SWIM

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use Coverings Resin Systems

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: : TOPCRET TECNOLOGIA EN REVESTIMIENTOS S.L.
Gran Vía de Les Corts Catalanes, 828
08013 Barcelona - España
Telephone : +34 932 741 208
Contact Person : info@topcret.com

1.4 Emergency telephone number

Toxicological Information Medical Service 91 562 04 20

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture EC regulation criteria 1272/2008 (CLP)

- ⚠ Warning, Skin Irrit. 2, Causes skin irritation.
- ⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.
- ⚠ Warning, Skin Sens. 1, May cause an allergic skin reaction.
- ⚠ Warning, STOT SE 3, May cause respiratory irritation.

Adverse physicochemical, human health and environmental effects:
No other hazards

2.2. Label elements

Symbols:



Warning

Hazard Statements:

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.

Precautionary Statements:

P261 Avoid breathing dust.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER.

Special Provisions:

None

Contents:

Portland cement, Cr(VI) < 2 ppm

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

See at paragraph 11 the additional information concerning crystalline silica

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 50% - < 75% free crystalline silica ($\varnothing > 10 \mu$)

CAS: 14808-60-7, EC: 238-878-4

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

>= 25% - < 50% Portland cement, Cr(VI) < 2 ppm

CAS: 65997-15-1, EC: 266-043-4

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H335

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.4.2/1 Skin Sens. 1 H317

>= 0.25% - < 0.49% free crystalline silica ($\varnothing < 10 \mu$)(*)

CAS: 14808-60-7, EC: 238-878-4

⚠ 3.9/2 STOT RE 2 H373

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Wash the mouth thoroughly and drink plenty of water. In case of disease consult a physician immediately and present this safety-data sheet.

In case of Inhalation:

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled, the product causes irritation in the airways. and if brought into contact with the skin, it causes appreciable inflammation, with erythema, scabs, and oedema.

If brought into contact with the eyes, the product causes serious eye injury, such as opacity of the cornea or lesions to the iris.

If brought into contact with the skin, the product may cause sensitisation of the skin.

This preparation contains cement. Contact between cement and body fluids (e.g. sweat and eye fluids) may cause irritation or burns.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

The product does not present a fire hazard

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Rapidly recover the product, wearing protective clothing.

Scoop into containers and seal for disposal.

After the product has been recovered, rinse the area and materials involved with water.

Wash with plenty of water.

- 6.4. Reference to other sections
See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
Avoid contact with skin and eyes and exposure to high dust concentration.
Avoid powder development and deposit
Use localized ventilation system.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.
Fine dust may form explosive mixture with air. Keep away from open flames, heat and sparks.
Do not remove shrink film in hazardous locations (because of risk of static charging/discharge)
- 7.2. Conditions for safe storage, including any incompatibilities
Always keep the containers tightly closed.
Incompatible materials:
Keep away from water or from damp surroundings.
Instructions as regards storage premises:
Adequately ventilated premises.
- 7.3. Specific end use(s)
None in particular

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
free crystalline silica ($\text{Ø} > 10 \mu$) - CAS: 14808-60-7
ACGIH - LTE mg/m³(8h): 0.025 mg/m³ - Notes: A2 (R) - Pulm fibrosis, lung cancer
Portland cement, Cr(VI) < 2 ppm - CAS: 65997-15-1
ACGIH - LTE mg/m³(8h): 1 mg/m³ - Notes: A4, (E,R) - Pulm func, resp symptoms, asthma
free crystalline silica ($\text{Ø} < 10 \mu$)(*) - CAS: 14808-60-7
EU - LTE mg/m³(8h): 0.025 mg/m³ - Notes: A2 (R) - Pulm fibrosis, lung cancer
ACGIH - LTE mg/m³(8h): 0,025 mg/m³ - Notes: A2 (R) - Pulm fibrosis, lung cancer
- DNEL Exposure Limit Values
N.A.
- PNEC Exposure Limit Values
N.A.
- 8.2. Exposure controls
Eye protection:
Safety goggles.
- Protection for skin:
Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.
- Protection for hands:
Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.
Neoprene gloves are suggested (0,5 mm) not recommended gloves: not waterproof gloves
- Respiratory protection:
Not needed for normal use.
A dust mask (P2) should be worn if above exposure limits
In case of insufficient ventilation use mask with B type filters (EN 14387).
- Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Thermal Hazards:

None

Environmental exposure controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	powder
Colour:	various
Odour:	typical
Odour threshold:	N.A.
pH:	N.A.
pH(water dispersion,10%):	12-12.5
Melting point / freezing point:	== °C
Initial boiling point and boiling range:	== °C
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	== °C
Evaporation rate:	N.A.
Vapour pressure:	== kPa (23°C)
Relative density:	1.4 g/cm ³ (23°C)
Vapour density (air=1):	N.A.
Solubility in water:	partly soluble
Solubility in oil:	soluble
Viscosity:	N.A.
Auto-ignition temperature:	== °C
Explosion limits(by volume):	==
Decomposition temperature:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Explosive properties:	==
Oxidizing properties:	N.A.

9.2. Other information

Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Route(s) of entry:

Ingestion: Yes

Inhalation: Yes

Contact: No

Toxicological information related to the product:

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

N.A.

Corrosive/Irritating Properties:

Skin:

The product can cause irritation by contact.

Eye:

The product can cause damage to eyes by contact

Sensitizing Properties:

Frequent and prolonged skin contacts with cement paste may cause dermatitis.

Carcinogenic Effects:

The IARC (International Agency for Research on Cancer) believes that the crystalline silica inhaled at the workplace can cause lung cancer in man.

However, it also points out that the cancer effect depends on the silica characteristics and on the biological-physical condition of the environment.

There is a large amount of information in support of the fact that increased risk of cancer is limited to persons suffering from silicosis.

In the current situation of studies, protection of workers from silicosis can be ensured by respecting the exposure limit values.

Mutagenic Effects:

No effects are known.

Teratogenic Effects:

No effects are known.

Additional Information:

Susceptibility to skin irritation and sensitization varies from person to person.

In a sensitized individual the allergic dermatitis may not appear until after several days or weeks of frequent and prolonged contact.

Therefore, even though the skin irritation potential is slight, skin contact should be avoided. Once sensitization has occurred, exposure of the skin to very small quantities of the material may cause erythema and edema.

For this reason, the contact with the skin should be avoided. Once sensitization has occurred, exposures to small amounts of material may cause erythema and edema locally.

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure

- i) STOT-repeated exposure
- j) aspiration hazard

SECTION 12: Ecological information

- 12.1. Toxicity
 - Adopt good industrial practices, so that the product is not released into the environment.
 - Not available data on the mixture
 - Biodegradability: not readily biodegradable
 - Biodegradability: no data available on the preparation.
 - N.A.
- 12.2. Persistence and degradability
 - N.A.
- 12.3. Bioaccumulative potential
 - N.A.
- 12.4. Mobility in soil
 - N.A.
- 12.5. Results of PBT and vPvB assessment
 - List of substances dangerous for the environment and corresponding classification:
 - 49 ppm tin sulphate
 - CAS: 7488-55-3
 - R50 Very toxic to aquatic organisms.
 - EC50 (Algae): 0.2 mg/l (72 hr)
 - vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects
 - Not available data on the mixture

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
 - Recover if possible. In so doing, comply with the local and national regulations currently in force.
 - 91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.
- Disposal of hardened product (EC waste code) : 17 01 01
Disposal of not hardened product (EC waste code) : 17 01 01
The suggested European waste code is just based on the composition of the product.
According to the specific process or application field a different waste code may be necessary.

SECTION 14: Transport information

- 14.1. UN number
 - Not classified as dangerous in the meaning of transport regulations.
 - UN Number: ==
- 14.2. UN proper shipping name
 - N.A.
- 14.3. Transport hazard class(es)
 - Rail/Road(RID/ADR): no dangerous good
 - ADR-Upper number: NA
 - Air (ICAO/IATA): no dangerous good
 - Sea (IMO/IMDG): no dangerous good
 - N.A.
- 14.4. Packing group
 - N.A.
- 14.5. Environmental hazards

- Marine pollutant: No
N.A.
- 14.6. Special precautions for user
N.A.
- 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
N.A.
No

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Dir. 2006/8/EC
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) n. 453/2010 (Annex I)
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

No restriction.

Restrictions related to the substances contained:

No restriction.

REACH Regulation (1907/2006) – All. XVII

The product contains Cr (VI) under the limitse established by annex. XVII pt.47. Respect the duration according to the information described on the packaging

Legislative Decree no. 81 of the 9th of April 2008 Title XI "Dangerous substances - Chapter I - Protection against chemical agents"

Directive 2000/39/CE and s.m.i. (Professional threshold limit)

Legislative Decree no. 152 of the 3rd of April 2006 and subsequent modifications and additions. (Environmental regulations)

Directive 105/2003/CE (Seveso III): N.A.

ADR Agreement – IMDG Code – IATA Regulation

VOC (2004/42/EC) : N.A. g/l

Social Dialogue on Respirable Crystalline Silica

On April 26, 2006 was signed a multi-sector social dialogue, based on a "Guide to Good Practices", on workers health protection who are in contact with products containing crystalline silica.

The text of the agreement published in G.U. European Union (2006 / C 279/02) and the "Guide to Good Practices", with attachments, are available on www.nepsi.eu website, they offer guidelines and useful information for handling products containing respirable crystalline silica.

15.2. Chemical safety assessment
No

SECTION 16: Other information

Text of phrases referred to under heading 3:

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Paragraphs modified from the previous revision:

SECTION 2: Hazards identification

SECTION 3: Composition/information on ingredients

SECTION 15: Regulatory information

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

Istituto Superiore di Sanità - Inventario Nazionale Sostanze Chimiche

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of
Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical
Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of
Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport
Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"
(ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
OEL:	European threshold limit value
VLE:	Threshold Limiting Value.
WGK:	German Water Hazard Class.
TSCA:	United States Toxic Substances Control Act Inventory
DSL:	DSL - Canadian Domestic Substances List

Version: 2.0

Date of issue/Date of revision: 30.10.2015

Date of previous issue: 15.03.2014

