

## SYSTEM

## BAXAB RUSTIC

### APPLICATION

### WALLS, INTERIOR AND EXTERIOR FLOORS

| ✓  | LAYERS                      | DRYING HOURS | RECOMMENDED TROWEL | SANDPAPER TYPE | CONSUMPTION                                                                                            |
|----|-----------------------------|--------------|--------------------|----------------|--------------------------------------------------------------------------------------------------------|
| 01 | TOPCRET BASE + FIBER MESH   | 2 HOURS      | METALLIC           | 150G           | (2 LAYERS)<br>BASE POWDER = 1.8 KG/M2<br>BASE LIQUID = 0.67 L/M2                                       |
| 02 | TOPCRET BASE                | 2 HOURS      | METALLIC           | 150G           |                                                                                                        |
| 03 | BAXAB® BASE (ex Baxab)      | 6 HOURS      | METALLIC           | 150G           | (1 LAYER)<br>BAXAB LIQUID (A) = 0.1L /M2<br>BAXAB LIQUID (B) = 0.2L/M2<br>BAXAB POWDER (C) = 0.4 KG/M2 |
| 04 | BAXAB® FINISH (ex Baxab NF) | 2 HOURS      | METALLIC/FLEXIBLE  | 150G           | (1 LAYER)<br>NF POWDER = 0.15 KG/M2<br>NF LIQUID = 0.10L/M2<br>NF HARDENER = 0.016 L/M2                |
| 05 | CRED® ARMOR                 | 2 HOURS      | PLASTIC            |                | (3 LAYERS)<br>COMPONENT 1 = 0.130 L/M2<br>COMPONENT 2 = 0.0195 L/M2                                    |
| 06 | CRED® ARMOR                 | 2 HOURS      | PLASTIC            |                |                                                                                                        |
| 07 | CRED® ARMOR                 | 2 HOURS      | PLASTIC            |                |                                                                                                        |

|                                                                                     |                                                                                                                                        |          |
|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|----------|
|  | TOTAL LAYERS                                                                                                                           | 7        |
|  | TOTAL DRYING TIME BETWEEN COATS                                                                                                        | 18 HOURS |
|  | 24 HOURS: LIGHT PEDESTRIAN TRAFFIC ALLOWED                                                                                             |          |
|  | YOU CAN NOW COVER YOUR FLOOR WITH A BREATHABLE MATERIAL (WE RECOMMEND MDF PANELS), REMOVE IT OVERNIGHT SO THE FLOOR CONTINUES TO HEAL. |          |
|  | 5 DAYS: NOW YOU CAN REPOSITION YOUR FURNITURE OR UNITS WITH NEW, CLEAN THE FELT PADS TO AVOID UNNECESSARY DAMAGE.                      |          |
|  | 7 DAYS: AVOID ACCUMULATION OF WATER AND IN CASE OF CONTACT WITH WATER, DRY IT AS SOON AS POSSIBLE.                                     |          |
|  | TYPE OF COLORING                                                                                                                       | POWDER   |